

MATERIAL SAFETY DATA SHEET



MSDS Name: LEVEL GRIP
MSDS Number: PF4508-01
Version Number: 0009
MSDS Date: 01/12/2007
Page Number: 1 of 5

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: LEVEL GRIP
CAS Number: MIXTURE
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: E
EPA Registration: NA

Company Identification: Acrylic Technologies, Inc.
P.O. Box 3425
Sunriver, OR 97707
Contact: CUSTOMER SERVICE
Telephone/Fax: (541) 617-9494 / (541) 617-9595
Emergency Phone (24 Hour): INFOTRAK
(800) 535-5053

Product Class: WATERBASE PAINT
Trade Name: LEVEL GRIP
Product Code: PF4508-01

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients	CAS Number	%	TSCA	Health	Fire	React	PP
(No hazardous ingredients known at this time.)							

SECTION III - HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Ingestion and/or inhalation.

CARCINOGENICITY:

This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

ACUTE (SHORT TERM) FOR PRODUCT:

EYES: Causes irritation.

SKIN: May cause skin irritation upon prolonged or repeated contact.

BREATHING: Causes slight irritation to nose and throat.

SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

CHRONIC (LONG TERM) FOR PRODUCT OR COMPONENTS:

Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

PERMISSIBLE EXPOSURE LEVEL FOR PRODUCT:

No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m³ as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

MATERIAL SAFETY DATA SHEET

MSDS Name: LEVEL GRIP
MSDS Number: PF4508-01
Version Number: 0009
MSDS Date: 01/12/2007
Page Number: 2 of 5

SECTION IV - FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.

IF ON SKIN: Flush skin with water.

IF SWALLOWED: Induce vomiting. Call a physician immediately. Give large amounts of water or milk.

Never give anything by mouth to an unconscious or convulsing person.

IF BREATHED: Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class: IIIB
Flash Range: >200F
Explosive Range: Not Applicable

EXTINGUISHING MEDIA:

Extinguishing media: Product is non-combustible.

SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece.

UNUSUAL FIRE & EXPLOSION HAZARDS:

None.

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILLS: Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.

LARGE SPILLS: Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.

NOTE: Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

PROTECT FROM FREEZING. Store above 40 deg. F. Frozen product may be irreversibly damaged. Keep container closed when not using. Agitate before using.

MATERIAL SAFETY DATA SHEET

MSDS Name: LEVEL GRIP
MSDS Number: PF4508-01
Version Number: 0009
MSDS Date: 01/12/2007
Page Number: 3 of 5

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

RESPIRATORY PROTECTION:

Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.

VENTILATION:

Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.

PROTECTIVE GLOVES:

None normally required. Use is advisable.

EYE PROTECTION:

Wear approved splashproof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.

OTHER PROTECTIVE EQUIPMENT:

Avoid contact with clothing, dried product may be irremovable.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	LIQUID
Appearance/Color:	WHITE
Odor:	MILD
Solubility (in water):	DISPERSIBLE
pH Value:	8.5 - 10.0
Boiling Range:	(WATER) 212.F (100.C)
Vapor Pressure (mmHg):	(WATER) 17. @ 68.F (20.C)
Melting Point:	Not Available
Evaporation Rate:	Unavailable
Vapor Density:	Non Volatile
Partition Coefficient	Not Available
% Volatile Volume	INCLUDING WATER 60.8%
Specific Gravity:	1.42633
VOC	SEE SECTION XVI
Molecular Weight:	MIXTURE

SECTION X - STABILITY AND REACTIVITY

Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur

INCOMPATIBILITY:
None

MATERIAL SAFETY DATA SHEET

MSDS Name: LEVEL GRIP
MSDS Number: PF4508-01
Version Number: 0009
MSDS Date: 01/12/2007
Page Number: 4 of 5

CONDITIONS TO AVOID:

Acids, strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

SECTION XI - TOXICOLOGICAL INFORMATION

Lethal Dose Information (ppm)

ADDITIONAL TOXICOLOGICAL DATA FOR PRODUCT AND/OR INGREDIENTS:

None known for product.

SECTION XII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:

Aquatic toxicity not available.

SECTION XIII - DISPOSAL CONSIDERATIONS

EPA Hazardous Waste Number NONE

WASTE DISPOSAL METHOD:

Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

UN Number: NONE
UN Pack Group: NA
UN Class: NA
ICAO/IATA Class: NONE
DOT Hazard Class: NOT HAZARDOUS

CANADIAN TDG/WHMIS INFORMATION:

PIN NUMBER: None
TDG: NA
TDG ACT CLASS: NA
WHMIS: D2B
OTHER NAMES: None

MATERIAL SAFETY DATA SHEET

MSDS Name: LEVEL GRIP
MSDS Number: PF4508-01
Version Number: 0009
MSDS Date: 01/12/2007
Page Number: 5 of 5

SECTION XV - REGULATORY INFORMATION

EEC Classification: Irritant

This product is not a listed hazardous substance.

SECTION XVI - OTHER INFORMATION

ADDITIONAL PRECAUTIONS AND NOTES:

Do not dilute or mix with other materials unless advised by supplier.

VOC INFORMATION

A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request.
VOC content: 0.14 lbs per gallon.