

MATERIAL SAFETY DATA SHEETMSDS Name: Grabber HangTite Spray Adhesive 747
Revision Date: January 1, 2010**1. Product and Company Identification**

Product Name: GRABBER® Professional Grade HANG TITE® Fast Tacking Construction Adhesive

Supplier: Grabber Construction Products
205 Mason Circle
Concord, CA 94520

Emergency telephone number: 800-424-9300

Technical phone number: 800-877-TURN (Concord, California) 8:00 a.m. - 4:00 p.m PST
Preparer: MWP, Phone: (314) 968-3222

2. Composition/Information on Ingredients

Item	Chemical Name	CAS Number	WT/WT% Less Than
01	ISOHEXANE	107-83-5	25.0 %
02	PROPANE	74-98-6	15.0 %
03	DIMETHYL ETHER	115-10-6	15.0 %
04	ACETONE	67-64-1	15.0 %
05	CYCLOHEXANE	110-82-7	15.0 %
06	ETHANE, 1,1-DIFLUORO	75-37-6	10.0 %
07	N-PENTANE	109-66-0	5.0 %

(See Section 16 for abbreviation legend)

3. Hazards Identification

*** EMERGENCY OVERVIEW ***: Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

EFFECTS OF OVEREXPOSURE

EYE CONTACT: Can cause severe irritation, redness, tearing, blurred vision.

SKIN CONTACT: Prolonged or repeated contact can cause moderate irritation defatting, dermatitis.

INHALATION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Possible cardiac arrhythmias at high concentrations.

INGESTION: No Information.

CHRONIC HAZARDS: Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage.

**PRIMARY ROUTE(S)
OF ENTRY:**

SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber HangTite Spray Adhesive 747
Revision Date: January 1, 2010

4. First Aid Measures

FIRST AID

EYE CONTACT: Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.
SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, makeup remover, mineral spirits, or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.
INHALATION: Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.
INGESTION: Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

5. Fire Fighting Measures

FLASH POINT: -156 F
(PENSKY-MARTENS C.C.)
LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT: 18.0 %
AUTOIGNITION TEMPERATURE: N.D.
EXTINGUISHING MEDIA: CO2, DRY CHEMICAL. FOAM, WATER FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol products - exposure to temperatures over 130F may cause containers to burst releasing highly flammable gas.
SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate sources of ignition & ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper container for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

7. Handling and Storage

HANDLING: Containers of this material may be hazardous when emptied, since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors from this product may be harmful or fatal.
STORAGE: Do not store above 120F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition. Do not store above 120F. Do not store in direct sunlight.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Provide sufficient mechanical ventilation (general and/or local exhaust) ventilation to maintain exposure below TLV(s).
RESPIRATORY PROTECTION: If work place exposure limits of product or any component is exceeded, use a NIOSH/MSHA approved respirator. Consult your safety equipment supplier for recommendations.
SKIN PROTECTION: Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations.
EYE PROTECTION: Wear safety glasses at minimum, more extensive protection may be necessary depending on how the product is to be used.
OTHER PROTECTIVE EQUIPMENT: Wear impervious clothing if bodily exposure is anticipated. Consult your safety supply vendor for recommendations.
HYGIENIC PRACTICES: Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber HangTite Spray Adhesive 747
Revision Date: January 1, 2010

9. Physical and Chemical Properties

BOILING RANGE : -44 - 177 F
VAPOR DENSITY : Is heavier than air
ODOR : MINT WHEN WET
ODOR THRESHOLD : N.D.
APPEARANCE : WHITE LIQUID
EVAPORATION RATE: Is faster than Butyl Acetate
SOLUBILITY IN H2O : NEGLIGIBLE
FREEZE POINT : N.D.
SPECIFIC GRAVITY: 0.7154
VAPOR PRESSURE : N.D.
pH @ 0.0 % : N.D.
PHYSICAL STATE : LIQUID
VISCOSITY : N.D.
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.

(See Section 16 for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.
INCOMPATIBILITY: Oxidizing agents, acids, alkali, alkaline earth metals, amines, reducing agents, strong oxidizers, very strong acid, caustic or oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: hydrofluoric acid and possibly carbonyl fluoride. carbon monoxide and carbon dioxide, various hydrocarbons, sulfur dioxide, sulfur monoxide,
HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.
STABILITY: This product is stable under normal storage conditions.

11. Toxicological Properties

No product or component toxicological information is available.

12. Ecological Information

ECOLOGICAL INFORMATION: No Information.

13. Disposal Considerations

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

14. Transportation Information

DOT PROPER SHIPPING NAME: Aerosols
DOT TECHNICAL NAME:
DOT HAZARD CLASS: 2.1
HAZARD SUBCLASS: NONE
DOT UN/NA NUMBER: UN1950
PACKING GROUP: NONE
RESP. GUIDE PAGE: 126
ADDITIONAL INFORMATION: For domestic ground and air shipment this product may be shipped as a Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D AIR designation. (our original cartons are preprinted with the ORM-D designation for ground shipment)

MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber HangTite Spray Adhesive 747
Revision Date: January 1, 2010

15. Regulatory Information

U.S. FEDERAL REGULATIONS: AS FOLLOWS
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA -

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD

FIRE HAZARD

PRESSURIZED GAS HAZARD

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Chemical Name	CAS Number	WT/WT% Less Than
CYCLOHEXANE	110-82-7	15.0 %

TOXIC SUBSTANCES CONTROL ACT: This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name	CAS Number
No information is available.	

U.S. STATE REGULATIONS: AS FOLLOWS -
CALIFORNIA PROPOSITION 65: WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

Chemical Name	CAS Number	WT/WT% Less Than
BENZENE	71-43-2	13 PPM
TOLUENE	108-88-3	8 PPM
ACETALDEHYDE	75-07-0	2 PPM
FORMALDEHYDE	50-00-0	2 PPM

INTERNATIONAL REGULATIONS: AS FOLLOWS -
CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.
TSCA Inventory: All components of this product are on the US TSCA inventory. On June 30, 1993 the OSHA Z-1-A table was revoked and OSHA reverted back to their prior exposure limits. The values on this MSDS reflect the roll back to the prior values. Some states may continue to enforce the 1993 limits. On June 16, 1995 EPA announced in a final rule that acetone would no longer be considered a VOC for air attainment standards. (it is now an exempt compound) The VOC calculations on this MSDS are based on acetone being an exempt compound. The June 16 rule also removed acetone from the list of SARA 313 reportable chemicals.

16. Other Information

HMIS RATINGS - HEALTH: 2
FLAMMABILITY: 4
REACTIVITY: 1
PREVIOUS MSDS
REVISION DATE: 07/11/06
REASON FOR REVISION: SCHEDULED UPDATE
VOLATILE BY WEIGHT: 82.8%
VOC CONTENT: 63.8 % BY WEIGHT, 456 GRAMS/LITER TOTAL PRODUCT, 545 GRAMS/LITER LESS WATER AND EXEMPT, 0.66 LBS/CAN
LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materials identification system have been included by Camie-Campbell Inc. in order to provide additional health and hazard classification information. The ratings recommend are based upon the criteria supplied by the developers of these rating systems, together with Camie-Campbell Inc.'s interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.