

# MATERIAL SAFETY DATA SHEET



MSDS Name: ACRYLITEX VAPOR PRIME  
MSDS Date: 06/15/06  
Page Number: 1 of 5

---

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: ACRYLITEX VAPOR PRIME  
CAS Number: MIXTURE  
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: E  
EPA Registration: NA

Company Identification: Acrylic Technologies, Inc.  
P.O. Box 3425  
Sunriver OR 97707  
Contact: CUSTOMER SERVICE  
Telephone/Fax: (541) 617-9494 / (541) 617-9595  
Emergency Phone (24 Hour): INFOTRAK  
(800) 535-5053

Product Class: WATERBASE PAINT  
Trade Name: DRYWALL VAPOR BARRIER

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients

CAS Number	%	TSCA	Health	Fire	React	PP
------------	---	------	--------	------	-------	----

(No hazardous ingredients known at this time.)

## SECTION III - HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Ingestion and/or inhalation.

CARCINOGENICITY:

This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

ACUTE (SHORT TERM) FOR PRODUCT:

EYES: Causes irritation.

SKIN: May cause skin irritation upon prolonged or repeated contact.

BREATHING: Causes slight irritation to nose and throat.

SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

CHRONIC (LONG TERM) FOR PRODUCT OR COMPONENTS:

Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: ACRYLITEX VAPOR PRIME  
MSDS Date: 06/15/06  
Page Number: 2 of 5

---

## PERMISSIBLE EXPOSURE LEVEL FOR PRODUCT:

No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m<sup>3</sup> as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

## SECTION IV - FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.

IF ON SKIN: Flush skin with water.

IF SWALLOWED: Induce vomiting. Call a physician immediately. Give large amounts of water or milk. Never give anything by mouth to an unconscious or convulsing person.

IF BREATHED: Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

## SECTION V - FIRE-FIGHTING MEASURES

Flammability Class III B  
Flash Range: >200F  
Explosive Range: Not Applicable

## EXTINGUISHING MEDIA:

Extinguishing media: Product is non-combustible.

## SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece.

## UNUSUAL FIRE & EXPLOSION HAZARDS:

None.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILLS: Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.

LARGE SPILLS: Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.

NOTE: Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

## SECTION VII - HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

PROTECT FROM FREEZING. Store above 40 deg. F. Frozen product may be irreversibly damaged. Keep container closed when not using. Agitate before using.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: ACRYLITEX VAPOR PRIME  
MSDS Date: 06/15/06  
Page Number: 3 of 5

---

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

### RESPIRATORY PROTECTION:

Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.

### VENTILATION:

Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.

### PROTECTIVE GLOVES:

None normally required. Use is advisable.

### EYE PROTECTION:

Wear approved splashproof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.

### OTHER PROTECTIVE EQUIPMENT:

Avoid contact with clothing, dried product may be irremovable.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	LIQUID
Appearance/Color:	WHITE
Odor:	MILD
Solubility (in water):	DISPERSIBLE
pH Value:	9.0-9.5
Boiling Range:	(WATER) 212.F (100.C)
Vapor Pressure (mmHg):	(WATER) 17. @ 68.F (20.C)
Melting Point:	Not Available
Evaporation Rate:	Unavailable
Vapor Density:	Non Volatile
Partition Coefficient	Not Available
% Volatile Volume	INCLUDING WATER 72.88%
Specific Gravity:	1.19226
VOC	SEE SECTION XVI
Molecular Weight:	MIXTURE

## SECTION X - STABILITY AND REACTIVITY

Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur

### INCOMPATIBILITY:

None

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: ACRYLITEX VAPOR PRIME  
MSDS Date: 06/15/06  
Page Number: 4 of 5

---

## CONDITIONS TO AVOID:

Acids, strong oxidizing agents.

## HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

## SECTION XI - TOXICOLOGICAL INFORMATION

Lethal Dose Information (ppm)

## ADDITIONAL TOXICOLOGICAL DATA FOR PRODUCT AND/OR INGREDIENTS:

None known for product.

## SECTION XII - ECOLOGICAL INFORMATION

## ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:

Aquatic toxicity not available.

## SECTION XIII - DISPOSAL CONSIDERATIONS

EPA Hazardous Waste Number NONE

## WASTE DISPOSAL METHOD:

Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

## SECTION XIV - TRANSPORT INFORMATION

UN Number	NONE
UN Pack Group	NA
UN Class	NA
ICAO/IATA Class	NONE
DOT Hazard Class	NOT HAZARDOUS

## CANADIAN TDG/WHMIS INFORMATION:

PIN NUMBER:	None
TDG:	NA
TDG ACT CLASS:	NA
WHMIS:	NA
OTHER NAMES:	None

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: ACRYLITEX VAPOR PRIME  
MSDS Date: 06/15/06  
Page Number: 5 of 5

---

## SECTION XV - REGULATORY INFORMATION

EEC Classification        Irritant

This product is not a listed hazardous substance.

## SECTION XVI - OTHER INFORMATION

### ADDITIONAL PRECAUTIONS AND NOTES:

Do not dilute or mix with other materials unless advised by supplier.

### VOC INFORMATION

A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request from Acrylic Technologies, Inc.. VOC Content: 0.15 lbs per gallon.