



# Acrylitex Interior Texture and Coating Submittal Documentation

Project: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Contractor: \_\_\_\_\_  
\_\_\_\_\_

Installer: \_\_\_\_\_  
\_\_\_\_\_

Supplier: John Wagner & Associates dba  
Grabber Construction Products  
866-237-GRAB(4722)

Distributor: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

# Specification Sheet

## Acrylitex Vapor Prime PF4506-01



**Manufacturer:** Acrylic Technologies, Inc.  
P.O. Box 8359, Bend, Oregon 97708  
Phone: 541.617.9494 / Fax: 541.617.9595

**Product Description:** Acrylitex Vapor Prime is a vapor barrier coating designed for use on interior walls. Vapor Prime is a non-breathing latex primer sealer applied in a production spray application which seals the wall with a perm rating of less than 1.0 in one coat.

**Coverage:** Coverage is 320 square feet per gallon when applied at 5 wet mils. Coverage rates will vary with mil thickness, applicator technique and type of spray tip (amount of fallout).

**Recommended Mil Rate:** Apply a minimum of 5 wet mils to achieve a less than 1 perm rating. Average dry time to touch is ½ hour. Dry time to re-coat is 2 hours.

**Packaging:** Available in 5 gallon and 55 gallon containers and 275 gallon totes.

**Colors:** Available in one color – White.

### **Preparation for Substrates of Gypsum, Plaster and Concrete:**

1. Surfaces must be clean, dry, sound and properly cured.
2. Surfaces must be free of sanding dust, dirt, oil, grease, mildew, fungus, efflorescence, loose paint or other contaminants.
3. Surfaces must be free of chalking, blistering, peeling, cracking and delaminating
4. Surface must be completely dry before application.

**Application Equipment:** Apply Acrylitex Vapor Prime with an airless sprayer. Respirator not required but recommended. Clean tools, equipment and skin with soapy water and rinse.

**Application:** Product is bucket ready. No thinning necessary.

Acrylitex Vapor Prime is designed for use as an undercoating for finish paint on interior walls and ceilings.

For additional information, contact Manufacturer.