



Submittal Sheet #0309041


Wafer Head Streaker

Product:	Item#	Description	Unit Pack
	31Z	Wafer Head Streaker 8X 9/16", Bulk	10 M
	31ZA	Wafer Head Streaker 8X 9/16", Bulk	10 M
	32Z	Wafer Head Streaker 8X 1", Bulk	5 M
	33Z	Wafer Head Streaker 8X 1-1/4", Bulk	5 M
	3138	Wafer Head Streaker 8X 1-1/2", Bulk	3 M
	3138Z	Wafer Head Streaker 8X 1 1/2", Bulk	3 M
	3151Z	Wafer Head Streaker 8X 2", Bulk	2.5 M
	3163Z	Wafer Head Streaker 8X 2 1/2", Bulk	2.5 M
	3176Z	Wafer Head Streaker 8X 3", Bulk	1 M

Application: The GRABBER Wafer Head Streaker™ is used to attach metal K lath, wire lath wood grounds, to lathers channel structural studs, and metal decks. Also used for attaching steel studs to runners, 20-25 gauge steel.

Description: Low profile wafer head, #2 Phillips Recess Drive, Fine 15 TPI, silver zinc finish with extra sharp point. Grabber Wafer Streakers in GrabberGard® Exterior Finish are ACQ Compliant.

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Wafer head is completely seated when the head base is flush with the work surface. Overdriving may result in failure of the fastener or stripping of the head recess.





Submittal Sheet #0309041

SUBMITTAL APPROVALS:

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by John Wagner Associates, Inc.: GRABBER

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.



Submittal Sheet #0309041

Wafer Head Streaker



Features:

Used for light gauge metal applications where low profile head exposure is desired. Streaker point means quick and easy penetration into metal (25-20 ga.), while wafer head provides greater bearing surface. The right screw for K-lath installation.



PRODUCT SPECIFICATIONS

Fastener Classification	Light Gauge Metal
Fastener Head	Wafer
Fastener Drive	#2 Phillips
Fastener Gauge	#8
Fastener Point	Streaker
Fastener Package Type	Packaged Screws
Fastener Package Weight	1lb Box, 5 Pound, Bulk Box

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Black/Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust

All GRABBER screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with SAE J78 and ASTM C 1002, as referenced in ICBO report ER-5280, and are approved for use by the Uniform Building Code. ©2005 John Wagner Associates, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX™, GRABBERGARD®, and SCAVENGER® are registered names or trademarks by John Wagner Associates, Inc., dba Grabber Construction Products.