



# SUBMITTAL SHEET

Submittal Sheet #GSCSF

## Grabber Acoustical Sound Sealant

Product:	Item#	Description	Unit Pack
	GSCSF	Grabber Acoustical Sound Sealant	12 tubes per case

<b>Product Features:</b>	<p>Exceeds the requirements of ASTM C834. Tested in accordance with ASTM E84, ASTM E90 and ASTM C919. Meets NFPA Class A fire rating.</p> <ul style="list-style-type: none"> <li>• Environmentally safe – VOC-compliant</li> <li>• Eliminates sound transmission and seals air gaps</li> <li>• Improves STC Values and upgrades sound quality</li> <li>• LEED EQ Credit 4.1: Low-Emitting-material, Adhesives and Sealants</li> <li>• SCAQMD Rule 1168 Compliant</li> <li>• UL 723 classified • Meets GS-36 requirements</li> <li>• Repairs cracks and eliminates rattles in drywall and plaster</li> <li>• Mold and mildew resistant</li> <li>• Easily tools with one pass</li> <li>• Cleans easily with water in wet state</li> <li>• Post-consumer recycled cartridge and carton</li> <li>• Paintable</li> </ul>
--------------------------	---

Sound Transmission Class (STC) Ratings:	Edge Detail	STC Rating	Comments
	Uncaulked	29	The open-edge track gave the STC value of 29 through direct leakage
	Single bead at the perimeter of one base layer	49	This bead closed void but did seal leakage around the joint between wallboard and track
	Two beads, one under each base layer of gypsum board	53	The beads closed void and sealed leakage around track

Note: Taken from ASTM C919. The test partitions of metal studs 610 mm (24 in.) on center, with double layers of 13 mm (0.5 in.)

Surface Burning Characteristics For Building materials:	FLAME	SMOKE	Comments
	O.O	O.O	Flame Smoke Tested as applied in two 1/4" diameter beads, 8 in. O.C.
	O.O	O.O	(Coverage: 2.8 percent of the exposed test sample area).



Submittal Sheet #GSCSF

**Submittal Approvals:**

---

**Job Name**

Contractor

Date

**TRADEMARKS:**

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

**Notice:**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be (30) days of the date it was or reasonably should have been discovered.