

# Acrylitex® Qwik Prep

Interior Precoat/Primer

**Acrylitex Qwik Prep is a fast drying drywall surfacer applied in a production spray application. The product has excellent hide and is very white in color so that you can see your pattern when spraying texture. Acrylitex Qwik Prep may be used as a precoat to uniform various porosities between drywall paper and joints or as a primer prior to paint to ensure the finish coat will be a smooth and uniform sheen.**

## For use on interior walls & ceilings

Uniforms various porosities between drywall paper and joints

Ensures the finish coat will be a smooth and uniform sheen



Acrylitex Qwik Prep is designed for use as an undercoating for texture and paint on interior walls and ceilings. Our liability is expressly limited to the replacement of defective product.



**QUICK DRYING - HIGH HIDE**

### Coverage

Approximately 350-400 square feet per gallon for optimum hide. Coverage rates will vary with mil thickness, applicator technique and type of spray tip (amount of fallout).

### Recommended Mil Rate

Apply 6 wet mils. Average dry time is 15-20 min. dependent on air temperature and relative humidity.

### Packaging

Available in 5 gallon and 55 gallon containers and 275 gallon totes.

### Colors

Available in one color – White.

### Application

May be applied with roller or airless sprayer. Product is bucket ready. No thinning necessary. Use at temperatures above 50 degrees F. Brush off dust or dirt on the wall. Apply as you would any primer.

### Cleanup

Clean tools and equipment with soapy water prior to drying.