

A **DURA WALL LEVEL 5** *Acrylitex* **DURA WALL** **TITANIUM TUFF**

- ▶ **Level 5 PVA primer**
- ▶ **Creates durable surface**
- ▶ **Replaces traditional skim coat**
- ▶ **Sandable**
- ▶ **Exceptional hold out**
- ▶ **Time saving spray application**

Acrylitex Dura Wall takes a level four finish to a level five in an easy spray application. Eliminates the intensive labor necessary with traditional skim coat. Acrylitex Dura Wall creates a uniform surface and minimizes the possibility of joint photographing showing through the final decoration.

One Step Application:

Spray 15 wet mils. Allow to dry. Spot prime areas that needed touch up.

Two Step Application:

Recommended two step application for maximum durability, custom projects and critical light areas: apply Acrylitex Dura Wall 15 wet mils. Touch up, sand touch up. Apply second coat Acrylitex Dura Wall 15 wet mils. 30 wet mils will leave 12 dry mils on the wall.

Coverage:

110 sq. ft. per gallon at 15 wet mils. Actual coverage can vary depending on factors such as substrate surface condition, spray techniques, procedures, coating uniformity and thickness.

Airless:

Use pump with output of at least 1 gallon per minute, 3300 PSI. Remove gun filter from gun. Acrylitex is a pump friendly product.

Tips:

Use whatever tip you are comfortable with. 519 – 625.

Product is bucket ready. No mixing. No thinning.

Manufacturer:

Acrylic Technologies, Inc. Bend, Oregon

For Technical Support call (541) 617-9494.

For Sales and Service call (800) 477-8876 Fax: (407) 295-9305